

Series N pressure regulators

Ports G1/8, G1/4



- » Knob with closure
- » Integral return exhaust (relieving)

Series N pressure regulators are available with G1/4 and G1/8 ports.
Their design incorporates a self relieving diaphragm so as to allow decremental adjustments.

GENERAL DATA

Construction diaphragm type Materials brass, technopolymer, NBR Ports G1/8 - G1/4 Weight Kg 0.316 Pressure gauge ports in - line or console (in any position) Mounting Operating temperature -5°C ÷ 50°C (with the dew point of the fluid lower than 2°C at the min. working temperature) Inlet pressure Outlet pressure 0.5 ÷ 10 bar(standard), 0 ÷ 2 bar; 0 ÷ 4 bar e 0.5 ÷ 7 bar Nominal flow see FLOW DIAGRAMS on the following pages Secondary pressure relieving with relieving (standard) without relieving Fluid compressed air

€ CAMOZZI





SERIES N

SIZE: 12 12

PORTS: 08 = G1/8 04 = G1/4

R = REGULATOR R

OPERATING PRESSURE: T

0 = 0.5 ÷ 10 bar (standard) 1 = 0 ÷ 4 bar 2 = 0 ÷ 2 bar 7 = 0.5 ÷ 7 bar

T = calibrated *
B = locked *

DESIGN TYPE: 0

0 = self-relieving 1 = non-relieving

* NOTE: IF THE REGULATOR IS CALIBRATED OR LOCKED, AFTER THE DESIGN TYPE ADD THE INLET PRESSURE " ■ " AND THE OUTLET PRESSURE " ● "

INLET PRESSURE:

■ = enter the SUPPLY pressure value

OUTLET PRESSURE:

• = enter the OUTLET pressure value for the LOCKED regulator or the maximum value of the ADJUSTABLE pressure for the CALIBRATED regulator

Example of a calibrated regulator with Inlet Pressure = 6.3 bar and Outlet Pressure = 4.5 bar Complete part number: N1204-RT0-6.3-4.5

Pressure regulators Series N





Calibrated or blocked regulators on request

PR01 = regulator without relieving PR02 = regulator with relieving











DIMENSIONS												
Mod.	А	В	С	F	G	I	L	М	N	R	S	U
N1208-R00	92	53	39	26	27	28	30X1,5	45	45	3	0÷6	G1/8
N1204-R00	92	53	39	26	27	28	30X1,5	45	45	3	0÷6	G1/4

SERIES N PRESSURE REGULATORS

FLOW DIAGRAMS





Flow diagram for model: N1208-R00

Pa = Inlet pressure (bar) Pr = Regulated pressure (bar)

Q = Flow (Nl/min)

Flow diagram for model: N1204-R00

Pa = Inlet pressure (bar) Pr = Regulated pressure (bar) Q = Flow (Nl/min)