

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A25A345

Datasheet creation date: 07/03/2025 18:49

Check the most updated document online 3 click here











TECHNICAL DATA

Series (mm)	25
Bore (mm)	25
Version	N = standard
Operation	2 = double acting
Materials	A = rolled stainless steel stem - stainless steel jacket
Construction	A = ring nut V + stem nut U
Stroke type	variable
Stroke (mm)	345
Rod seals material	= standard
Extended rod (mm)	0

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A25A345



DIMENSIONS

EW (mm) 16 KW (mm) 10 BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
EE G1/8 ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
ØD2 (mm) 10 L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
L1 (mm) 486.5 XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
XC (mm) 449 L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
L2 (mm) 414.5 AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0
L3 (mm) 20 L4 (mm) 8.0
L4 (mm) 8.0
L5 (mm) 22
L (mm) 12
WF (mm) 28
L6 (mm) 16
L7 (mm) 50
KV (mm) 32
SW (mm) 9
D (mm) 27.0
D3 (mm) 27