

## Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A25A416

Datasheet creation date: 07/03/2025 18:50

Check the most updated document online 3 click here











## TECHNICAL DATA

Series (mm)	25
Bore (mm)	25
Version	N = standard
Operation	2 = double acting
Materials	A = rolled stainless steel stem - stainless steel jacket
Construction	A = ring nut V + stem nut U
Stroke type	variable
Stroke (mm)	416
Rod seals material	= standard
Extended rod (mm)	0

## Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A25A416



## DIMENSIONS

EW (mm) 16  KW (mm) 10  BE M22x1,5  KK M10x1,25  ØCD (mm) 8  D1 (mm) 27.0  EE G1/8  ØD2 (mm) 10  L1 (mm) 557.5  XC (mm) 520  L2 (mm) 485.5  AM (mm) 22  L3 (mm) 20  L4 (mm) 8.0  L5 (mm) 22  L (mm) 48.0  L5 (mm) 22  L (mm) 42
BE       M22x1,5         KK       M10x1,25         ØCD (mm)       8         D1 (mm)       27.0         EE       G1/8         ØD2 (mm)       10         L1 (mm)       557.5         XC (mm)       520         L2 (mm)       485.5         AM (mm)       22         L3 (mm)       20         L4 (mm)       8.0         L5 (mm)       22
KK M10x1,25  ØCD (mm) 8  D1 (mm) 27.0  EE G1/8  ØD2 (mm) 10  L1 (mm) 557.5  XC (mm) 520  L2 (mm) 485.5  AM (mm) 22  L3 (mm) 20  L4 (mm) 8.0  L5 (mm) 22
ØCD (mm)     8       D1 (mm)     27.0       EE     G1/8       ØD2 (mm)     10       L1 (mm)     557.5       XC (mm)     520       L2 (mm)     485.5       AM (mm)     22       L3 (mm)     20       L4 (mm)     8.0       L5 (mm)     22
D1 (mm)       27.0         EE       G1/8         ØD2 (mm)       10         L1 (mm)       557.5         XC (mm)       520         L2 (mm)       485.5         AM (mm)       22         L3 (mm)       20         L4 (mm)       8.0         L5 (mm)       22
EE       G1/8         ØD2 (mm)       10         L1 (mm)       557.5         XC (mm)       520         L2 (mm)       485.5         AM (mm)       22         L3 (mm)       20         L4 (mm)       8.0         L5 (mm)       22
ØD2 (mm)     10       L1 (mm)     557.5       XC (mm)     520       L2 (mm)     485.5       AM (mm)     22       L3 (mm)     20       L4 (mm)     8.0       L5 (mm)     22
L1 (mm) 557.5  XC (mm) 520  L2 (mm) 485.5  AM (mm) 22  L3 (mm) 20  L4 (mm) 8.0  L5 (mm) 22
XC (mm)     520       L2 (mm)     485.5       AM (mm)     22       L3 (mm)     20       L4 (mm)     8.0       L5 (mm)     22
L2 (mm)     485.5       AM (mm)     22       L3 (mm)     20       L4 (mm)     8.0       L5 (mm)     22
AM (mm) 22 L3 (mm) 20 L4 (mm) 8.0 L5 (mm) 22
L3 (mm) 20 L4 (mm) 8.0 L5 (mm) 22
L4 (mm) 8.0 L5 (mm) 22
L5 (mm) 22
L (mm) 12
WF (mm) 28
<b>L6 (mm)</b> 16
<b>L7 (mm)</b> 50
KV (mm) 32
<b>SW (mm)</b> 9
<b>D</b> (mm) 27.0
D3 (mm) 27