

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A32A500

Datasheet creation date: 07/03/2025 18:57

Check the most updated document online 3 click here











TECHNICAL DATA

Series (mm)	25
Bore (mm)	32
Version	N = standard
Operation	2 = double acting
Materials	A = rolled stainless steel stem - stainless steel jacket
Construction	A = ring nut V + stem nut U
Stroke type	standard
Stroke (mm)	500
Rod seals material	= standard
Extended rod (mm)	0

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N2A32A500



DIMENSIONS

KW (mm) 8 BE M30x1,5 KK M10x1,25 ØCD (mm) 12 D1 (mm) 33.6 EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	EIA/ (mm)	26
BE M30x1,5 KK M10x1,25 ØCD (mm) 12 D1 (mm) 33.6 EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	EW (mm)	
KK M10x1,25 ØCD (mm) 12 D1 (mm) 33.6 EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	KW (mm)	
ØCD (mm) 12 D1 (mm) 33.6 EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	BE	M30x1,5
D1 (mm) 33.6 EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 22 L (mm) 48 KV (mm) 48 KV (mm) 0	KK	M10x1,25
EE G1/8 ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	ØCD (mm)	12
ØD2 (mm) 12 L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	D1 (mm)	33.6
L1 (mm) 641.5 XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	EE	G1/8
XC (mm) 605 L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	ØD2 (mm)	12
L2 (mm) 569.0 AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L1 (mm)	641.5
AM (mm) 20 L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	XC (mm)	605
L3 (mm) 19 L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L2 (mm)	569.0
L4 (mm) 7.5 L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	AM (mm)	20
L5 (mm) 22 L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L3 (mm)	19
L (mm) 12 WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L4 (mm)	7.5
WF (mm) 28 L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L5 (mm)	22
L6 (mm) 15 L7 (mm) 48 KV (mm) 0	L (mm)	12
L7 (mm) 48 KV (mm) 0	WF (mm)	28
KV (mm) 0	L6 (mm)	15
	L7 (mm)	48
	KV (mm)	0
SW (mm) 10	SW (mm)	10
D (mm) 36.5	D (mm)	36.5
D3 (mm) 35	D3 (mm)	35