

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N3A25A090

Datasheet creation date: 07/03/2025 18:54

Check the most updated document online 3 click here











TECHNICAL DATA

Series (mm)	25
Bore (mm)	25
Version	N = standard
Operation	2 = double acting, through rod
Materials	A = rolled stainless steel stem - stainless steel jacket
Construction	A = ring nut V + stem nut U
Stroke type	variable
Stroke (mm)	90
Rod seals material	= standard
Extended rod (mm)	0

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N3A25A090



DIMENSIONS

EW (mm) 16 KW (mm) 10 BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0 L2 (mm) 159.5
BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
EE G1/8 ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
ØD2 (mm) 10 L1 (mm) 349.5 XC (mm) 0
L1 (mm) 349.5 XC (mm) 0
XC (mm) 0
1.2 (mm) 159.5
22 (11111)
AM (mm) 22
L3 (mm) 20
L4 (mm) 8.0
L5 (mm) 22
L (mm) 12
WF (mm) 28
L6 (mm) 16
L7 (mm) 50
KV (mm) 32
SW (mm) 9
D (mm) 27.0
D3 (mm) 27