

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N3A25A125

Datasheet creation date: 07/03/2025 18:54

Check the most updated document online 3 click here











TECHNICAL DATA

| Series (mm) | 25 |
|--------------------|--|
| Bore (mm) | 25 |
| Version | N = standard |
| Operation | 2 = double acting, through rod |
| Materials | A = rolled stainless steel stem - stainless steel jacket |
| Construction | A = ring nut V + stem nut U |
| Stroke type | standard |
| Stroke (mm) | 125 |
| Rod seals material | = standard |
| Extended rod (mm) | 0 |

Minicylinders - Series 16 - 23 - 24 - 25

Product code: 25N3A25A125



DIMENSIONS

| EW (mm) 16 KW (mm) 10 BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
|--|
| BE M22x1,5 KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
| KK M10x1,25 ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
| ØCD (mm) 8 D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
| D1 (mm) 27.0 EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
| EE G1/8 ØD2 (mm) 10 L1 (mm) 419.5 |
| ØD2 (mm) 10 L1 (mm) 419.5 |
| L1 (mm) 419.5 |
| ` ' |
| |
| XC (mm) 0 |
| L2 (mm) 194.5 |
| AM (mm) 22 |
| L3 (mm) 20 |
| L4 (mm) 8.0 |
| L5 (mm) 22 |
| L (mm) 12 |
| WF (mm) 28 |
| L6 (mm) 16 |
| L7 (mm) 50 |
| KV (mm) 32 |
| SW (mm) 9 |
| D (mm) 27.0 |
| D3 (mm) 27 |