

## Rodless cylinders - Series 50

Product code: 50M2P16A1250

Datasheet creation date: 08/03/2025 11:39

Check the most updated document online 3 click here









## TECHNICAL DATA

Series	50	
Version	M = magnetic standard	
Operation	2 = double-acting cushioned	
Materials	P = anodized AL profile tube, NBR and Polyurethane seals, standard carriage	
Diameter (mm)	16	
Construction (mm)	A = standard	
Stroke (mm)	1250	



## **Rodless cylinders - Series 50**

Product code: 50M2P16A1250





## DIMENSIONS

A (mm)	5
B (mm)	32
C (mm)	48
D (mm)	64
E (mm)	76
F	M4
F1 (mm)	8
G (mm)	6
H (mm)	2.0
I (mm)	M5
L (mm)	5.3
L1 (mm)	100
M (mm)	16
N (mm)	15
P (mm)	M3
P1 (mm)	3
Q (mm)	8.0
R (mm)	42.5
S (mm)	28.0
S1 (mm)	27
T (mm)	13.5
U (mm)	10
V (mm)	18

Z (mm)	24
Y (mm)	24.5
W (mm)	27
AA (mm)	29
BB (mm)	30
TG (mm)	18
SW2 (mm)	4
B1 (mm)	36
B2 (mm)	4
B3 (mm)	4.5
B4 (mm)	25
B5 (mm)	40
B6 (mm)	76
B7 (mm)	50