

## Direct acting solenoid valves - Series PL

Product code: PL000-9B7-PF22-OX1

Datasheet creation date: 10/03/2025 11:42

Check the most updated document online [click here](#)




### TECHNICAL DATA

<b>Series</b>	PL
<b>Valvebody</b>	0 = interface
<b>Number of positions</b>	00 = ISO 15218 or Series PD interface
<b>Number of ways - Functions</b>	9 = 2/2-way - NO
<b>Valve connections</b>	B = series PD interface - 2/2-way
<b>Orifice diametres</b>	7 = Ø 1.6 mm
<b>Materials</b>	PF = PBT body - FKM seals
<b>Electric connection</b>	2 = industrial standard connection (9.4 mm)
<b>Voltage - Absorbed power</b>	2 = 12 V DC - 2.7 W - PA
<b>Fixing</b>	= fixing screws for metal
<b>Manual override</b>	= not required or not applicable
<b>Option</b>	OX1 = for oxygen (non-volatile residue less than 550 mg / m <sup>2</sup> )

## Direct acting solenoid valves - Series PL

Product code: PL000-9B7-PF22-OX1



### DIMENSIONS

<b>Series</b>	PL
<b>Valvebody</b>	0 = interface
<b>Number of positions</b>	00 = ISO 15218 or Series PD interface
<b>Number of ways - Functions</b>	9 = 2/2-way - NO
<b>Valve connections</b>	B = series PD interface - 2/2-way
<b>Orifice diametres</b>	7 = Ø 1.6 mm
<b>Materials</b>	PF = PBT body - FKM seals
<b>Electric connection</b>	2 = industrial standard connection (9.4 mm)
<b>Voltage - Absorbed power</b>	2 = 12 V DC - 2.7 W - PA
<b>Fixing</b>	= fixing screws for metal
<b>Manual override</b>	= not required or not applicable
<b>Option</b>	OX1 = for oxygen (non-volatile residue less than 550 mg / m <sup>2</sup> )