

Short-stroke cylinders - Series QL

Product code: QLN2A012A025

Datasheet creation date: 09/03/2025 23:22

Check the most updated document online 3 click here







TECHNICAL DATA

Series	QL
Version	N = Non magnetic
Function	2 = double - acting
Materials	A = rolled stainless steel rod - AL profile
Construction type	A = Standard
Diameter (mm)	Ø12
Stroke (mm)	25
Rod	= Standard
Certification	= Standard



Short-stroke cylinders - Series QL

Product code: QLN2A012A025

DIMENSIONS

D (mm) 0.0 E (mm) 25.0 G (mm) 17.0 H (mm) 7.5 H1 (mm) 5.0 J M4x0.7 K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N1 (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0		
E (mm) 25.0 G (mm) 17.0 H (mm) 7.5 H1 (mm) 5.0 J M4x0.7 K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	C (mm)	6
G (mm) 17.0 H (mm) 7.5 H1 (mm) 5.0 J M4x0.7 K (mm) 6.5 L (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	D (mm)	0.0
H (mm) 7.5 H1 (mm) 5.0 J M4x0.7 K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	E (mm)	25.0
H1 (mm) 5.0 J M4x0.7 K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	G (mm)	17.0
J M4x0.7 K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	H (mm)	7.5
K (mm) 6.5 L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	H1 (mm)	5.0
L (mm) 3.5 L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	J	M4x0.7
L1 (mm) 11.0 M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	K (mm)	6.5
M (mm) 6 M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	L (mm)	3.5
M1 (mm) 6.0 N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	L1 (mm)	11.0
N (mm) 20.5 P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	M (mm)	6
P M3x0.5 Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	M1 (mm)	6.0
Q M5x0.8 SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	N (mm)	20.5
SW (mm) 5 TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	P	M3x0.5
TG (mm) 15.5 Z (mm) 0 W (mm) 14.0	Q	M5x0.8
Z (mm) 0 W (mm) 14.0	SW (mm)	5
W (mm) 14.0	TG (mm)	15.5
	Z (mm)	0
	W (mm)	14.0
KK M5x0.8	KK	M5x0.8
AM (mm) 10.5	AM (mm)	10.5